

SAFETY DATA SHEET

Section 1. Identification

CHS Inc. P.O. Box 64089 Mail station 525 St. Paul, MN 55164-0089		Transportation Emergency (CHEMTREC) Technical Information SDS Information	:	1-800-424-9300 1-651-355-8443 1-651-355-8445
Product name	: Synthetic Transmission Fluid CD-50	SDS no.	:	1315-FO875595
Common name	: Transmission Oil SAE 50	Revision date	:	03/11/2014
Chemical name	: Lubricating oil.	Chemical formula	:	Mixture
Chemical family	: Hydrocarbon.			

Relevant identified uses of the substance or mixture and uses advised against

Not available.

					_		
OSHA/HCS status	: This material is	considered ha	azardous by	/ the OSHA Hazard (Commu	nication Standard (29 CFF	R 1910.1200).
Classification of the substance or mixture	: SKIN CORROS	SION/IRRITAT	ION - Cate	gory 2			
GHS label elements							
Hazard pictograms Signal word	: Warning						
Hazard statements	: Causes skin irr	itation.					
Precautionary statements							
General	: Read label before label at hand.	ore use. Keep	out of read	h of children. If med	lical adv	vice is needed, have produ	ict container or
Hazardous Material Information	System (U.S.A.)	Health :	2 *	Flammability :	1	Physical hazards: 0	
National Fire Protection Associa	tion (U.S.A.)	Health :	2	Flammability :	1	Instability: 0	
	Section 3. C	omposition	/informa	tion on ingredi	ents		

Section 2. Hazards identification

Substance/mixture	: Mixture						
Chemical name	: Lubricating oil.						
Other means of identification	: Transmission Oil SAE 50						
Ingredient name		%	CAS number				
Butene, homopolymer White mineral oil (petroleum)		10 - 30 1 - 5	9003-29-6 8042-47-5				

White mineral oil (petroleum)

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first air	<u>d measures</u>
Eye contact	: If material comes in contact with the eyes, immediately wash the eyes with large amounts of water for 15
Inhalation	minutes, occasionally lifting the lower and upper lids. Get medical attention. If person breathes in large amounts of material, move the exposed person to fresh air at once. If breathing has
Innalation	stopped, perform artificial respiration. Keep the person warm and at rest. Get medical attention as soon as possible.
Skin contact	: If the material comes in contact with the skin, wash the contaminated skin with soap and water promptly. If the
	material penetrates through clothing, remove the clothing and wash the skin with soap and water promptly. If irritation persists after washing, get medical attention immediately.
Ingestion	: If material has been swallowed, do not induce vomiting. Get medical attention immediately.
Most important symptoms/effect	s, acute and delayed
Potential acute health effects	
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation.
Ingestion	: Irritating to mouth, throat and stomach.
Over-exposure signs/symptom	<u>s</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation, watering, redness.
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation, coughing.
Skin contact	: Adverse symptoms may include the following: irritation, redness.
Ingestion	: No known significant effects or critical hazards.
Indication of immediate medica	al attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
See toxicological information (Section 11)
	Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	 Use water spray to cool fire exposed surfaces and to protect personnel. Foam, dry chemical or water spray (fog) to extinguish fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: Toxic fumes gases or vapors may evolve on burning.
Hazardous thermal decomposition products	 Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	 When fighting fires wear full turnout gear and self contained breathing apparatus. Water may cause splattering. Material floats on water.
Special protective equipment for fire-fighters	: Not applicable.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Keep unnecessary and unprotected personnel from entering. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Methods and materials for containment and cleaning up

Spill

: Contain with dikes or absorbent to prevent migration to sewers/streams. Take up small spill with dry chemical absorbent; large spills may require pump or vacuum prior to absorbent. May require excavation of severely contaminated soil.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	 Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
Conditions for safe storage, including any incompatibilities	: Do not store above the following temperature: 80°C (176°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	Exposure limits			
White mineral oil (petroleum)	ACGIH TLV (United States, 6/2013). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 4/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours.				
Appropriate engineering controls	e only with adequate ventilation.				
Environmental exposure controls	nissions from ventilation or work process equipment should be checked to ensure they comply w quirements of environmental protection legislation.	/ith the			
Individual protection measures					
Hygiene measures	ash hands, forearms and face thoroughly after handling chemical products, before eating, smoki I lavatory and at the end of the working period. Ensure that eyewash stations and safety showe the workstation location.				
Eye/face protection	commended: Splash goggles and a face shield, where splash hazard exists.				
Skin protection					
Hand protection	8 hours (breakthrough time): Nitrile gloves.				
Body protection	: Recommended: Long sleeved coveralls.				
Other skin protection	commended: Impervious boots.				
Respiratory protection	rentilation is inadequate, use a NIOSH-certified respirator with an organic vapor cartridge and Peter.	95 particulate			

Section 9. Physical and chemical properties

Appearance		Relative density	: 0.9 to 0.92
Physical state	: Liquid.	Evaporation rate	: <1 (Ether. = 1)
Color	: Amber.	Solubility	: Insoluble in the following materials: cold water and hot water.
Odor	: Mild.	Solubility in water	: Insoluble
Odor threshold	: Not available.	Partition coefficient: n-	: Not available.
рН	: Not available.	octanol/water	
Melting point	: Not available.	Auto-ignition temperature	: >398.88°C (>750°F)
Boiling point	: Not available.	Decomposition temperature	: Not available.
Flash point	: Closed cup: >235°C (>455°F)	SADT	: Not available.
Flammability	: Not available.	Viscosity	: Not available.
Lower and upper	: Not available.	Vapor pressure	: <0.13 kPa (<1 mm Hg) [(68°F)]
explosive (flammable) limits		Vapor density	Not available.

:	No specific test data related to reactivity available for this product or its ingredients.
:	The product is stable.
:	Under normal conditions of storage and use, hazardous reactions will not occur.
:	No specific data.
:	Reactive or incompatible with the following materials: oxidizing materials.
:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 10. Stability and reactivity

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
White mineral oil (petroleum)	LD50 Oral	Rat	>5000 mg/kg	-
Irritation/Corrosion				
Skin	: There is no data available.			
Eyes	: There is no data available.			
Respiratory	: There is no data available.			
<u>Sensitization</u>				
Skin	: There is no data available.			
Respiratory	: There is no data available.			
<u>Mutagenicity</u>				
There is no data available.				
Carcinogenicity				
There is no data available.				
Reproductive toxicity				
There is no data available.				
<u>Teratogenicity</u>				
There is no data available.				
Specific target organ toxicity (sir	<u>ngle exposure)</u>			
There is no data available.				
Specific target organ toxicity (re	<u>peated exposure)</u>			
There is no data available.				
Aspiration hazard				
Nomo		Boo		

Name	Result
Butene, homopolymer	ASPIRATION HAZARD - Category 1
White mineral oil (petroleum)	ASPIRATION HAZARD - Category 1

Information on the likely routes of : Dermal contact. Eye contact. Inhalation. Ingestion. exposure

Section 12. Ecological information

Toxicity

There is no data available.

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name	L	.ogP _{ow}			BCF			Potential	
Butene, homopolymer White mineral oil (petroleum)		7.6 to 7.8 314 to 1882 high >6 - high							
Mobility in soil									
Soil/water partition coefficient (Koc) : There is no data available.									
Other adverse effects	Other adverse effects : No known significant effects or critical hazards.								
		5	Section 13. D	Disposal	consider	ations	6		
Disposal methods : Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.									
			Section 14.	Transpo	ort inform	ation]
DOT IDENTIFICATION NUM	BER Not ap	oplicable.	DOT pro	per shippi	ng name	Not a	pplicable.		
DOT Hazard Class(es) No	ot applicable.		PG No	ot applicable	э.	DOT	EMER. RESPONS	SE GUIDE NO. N	ot available.
			Section 15. I	Regulato	ory inform	nation	l		
U.S. Federal regulations	:	United Sta Clean Wat) CDR Exempt/P ates inventory (ter Act (CWA) 3 ter Act (CWA) 3	TSCA 8b): 07: Ethylbe	All compone	ents are	ined Iisted or exempte	d.	
Clean Air Act Section 602 Cla Clean Air Act Section 602 Cla Clean Air Act Section 112(b) H	ss II Substa	nces :	Not listed Not listed ts (HAPs)		st II Chemic	•	ecursor Chemical sential Chemical	•	listed listed
SARA 302/304									
Composition/information	on ingredie	<u>ents</u>							
No products were found.	-								
SARA 304 RQ	:	Not applica	able.						
SARA 311/312									
Classification	:	Immediate	(acute) health h	azard					
Composition/information	on ingredie	<u>ents</u>							
Name			%	Fire hazard	Sudden release of pressure	:	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Butene, homopolymer			10 - 30	No.	No.		No.	Yes.	No.
SARA 313	:	This produ the Emerge	ıct (does/not) cor ency Planning ar	ntain toxic c nd Commur	hemicals su	bject to -Know	the reporting requ Act of 1986 and of	uirements of SAR. f 40 CFR 372.	A Section 313 of
Product name				CAS num	ber	%			
Not applicable.									
SARA 313 notifications mu the notice attached to copie					nd redistribu	ition of	the SDS shall incl	ude copying and r	edistribution of
State regulations									
Massachusetts	:	None of the	e components a	re listed.					
New York	:	None of the	e components a	re listed.					
New Jersey	:	The followi paraffinic	ing components	are listed: \	White minera	al oil (pe	etroleum); Distillate	es (petroleum), hy	drotreated heavy
Pennsylvania	:	None of the	e components a	re listed.					
California Prop. 65 : WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer.									

Synthetic Transmission Fluid CD-50

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Ethylbenzene	Yes.			No.
Paraffin oils	Yes.		54 µg/day (inhalation) No.	No.

Section 16. Other information

Revision date	: 03/11/2014	Supersedes	: 03/23/2009
Revised Section(s)	: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16.	Prepared by	: KMK Regulatory Services Inc.
Notice to reader			

Notice to reader THE INFORMATION CONTAINED IN THIS SDS RELATES ONLY TO THE SPECIFIC MATERIAL IDENTIFIED. IT DOES NOT COVER USE OF THAT MATERIAL IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PARTICULAR PROCESS. IN COMPLIANCE WITH 29 C.F.R. 1910.1200(g), CHS HAS PREPARED THIS SDS IN SEGMENTS, WITH THE INTENT THAT THOSE SEGMENTS BE READ TOGETHER AS A WHOLE WITHOUT TEXTUAL OMISSIONS OR ALTERATIONS. CHS BELIEVES THE INFORMATION CONTAINED HEREIN TO BE ACCURATE, BUT MAKES NO REPRESENTATION, GUARANTEE, OR WARRANTY, EXPRESS OR IMPLIED, ABOUT THE ACCURACY, RELIABILITY, OR COMPLETENESS OF THE INFORMATION OR ABOUT THE FITNESS OF CONTENTS HEREIN FOR EITHER GENERAL OR PARTICULAR PURPOSES. PERSONS REVIEWING THIS SDS SHOULD MAKE THEIR OWN DETERMINATION AS TO THE MATERIAL'S SUITABILITY AND COMPLETENESS FOR USE IN THEIR PARTICULAR APPLICATIONS.



