

SAFETY DATA SHEET

Section 1. Identification

CHS Inc. Transportation Emergency (CHEMTREC) : 1-800-424-9300 CCN23163

P.O. Box 64089 Technical Information : 1-651-355-8442 Mail station 525

St. Paul, MN 55164-0089 SDS Information : 1-651-355-8445

Common name : Diesel Engine Oil 15W-40 Revision date : 01/19/2025

Chemical name : Lubricating oil. Chemical formula : Mixture

Chemical family : Hydrocarbon.

Relevant identified uses of the substance or mixture and uses advised against

Lubricant.

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

: SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H319 - Causes serious eye irritation.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or

label at hand.

Prevention : Wear eye or face protection. Wash hands thoroughly after handling.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage : Not applicable.

Disposal : Not applicable.

Hazards not otherwise classified : None known.

Hazardous Material Information System (U.S.A.) Health: 1 / Flammability: 1 Physical hazards: 0

National Fire Protection Association (U.S.A.) Health: 1 Flammability: 1 Instability: 0

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Chemical name : Lubricating oil.

Other means of identification : Diesel Engine Oil 15W-40

Ingredient name	%	CAS number
, , , , , , , , , , , , , , , , , , ,	≥25 - ≤50 ≥10 - ≤25 ≥1 - ≤3	64742-54-7 64742-55-8 64742-65-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : If material comes in contact with the eyes, immediately wash the eyes with large amounts of water for 15

minutes, occasionally lifting the lower and upper lids. Get medical attention.

Inhalation : If person breathes in large amounts of material, move the exposed person to fresh air at once. If breathing has

stopped, perform artificial respiration. Keep the person warm and at rest. Get medical attention as soon as

possible.

Skin contact : If the material comes in contact with the skin, wash the contaminated skin with soap and water promptly. If the

material penetrates through clothing, remove the clothing and wash the skin with soap and water promptly. If

irritation persists after washing, get medical attention immediately.

Ingestion : If material has been swallowed, do not induce vomiting. Get medical attention immediately.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: Causes serious eye irritation.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following: pain or irritation, watering, redness.

Inhalation : Adverse symptoms may include the following: respiratory tract irritation, coughing.

Skin contact: Adverse symptoms may include the following: irritation, redness.

Ingestion: No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested

or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the

person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use water spray to cool fire exposed surfaces and to protect personnel. Foam, dry chemical or

water spray (fog) to extinguish fire.

Unsuitable extinguishing media

Specific hazards arising from the chemical

Toxic fumes gases or vapors may evolve on burning.

Hazardous thermal decomposition products

: No specific data.

None known.

Special protective actions for fire-fighters

When fighting fires wear full turnout gear and self contained breathing apparatus. Water may cause splattering. Material floats on water.

Special protective equipment for fire-fighters

: Not applicable.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Keep unnec

: Keep unnecessary and unprotected personnel from entering. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Methods and materials for containment and cleaning up

Spill : Contain with dikes or absorbent to prevent migration to sewers/streams. Take up small spill with dry chemical absorbent; large spills may require pump or vacuum prior to absorbent. May require excavation of severely

contaminated soil.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Advice on general occupational hygiene

 Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 113°C (235.4°F). Odorous and toxic fumes may form from the decomposition of this product if stored at excessive temperatures for extended periods of time. Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	OSHA PEL (United States, 6/2016).
	TWA: 5 mg/m ³ 8 hours.
	ACGIH TLV (United States, 3/2017).
	TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction
	NIOSH REL (United States, 10/2016).
	TWA: 5 mg/m³ 10 hours. Form: Mist
	STEL: 10 mg/m³ 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated light paraffinic	OSHA PEL (United States, 6/2016).
	TWA: 5 mg/m³ 8 hours.
	ACGIH TLV (United States, 3/2017).
	TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction
	NIOSH REL (United States, 10/2016).
	TWA: 5 mg/m³ 10 hours. Form: Mist
	STEL: 10 mg/m³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OSHA PEL (United States, 6/2016).
	TWA: 5 mg/m³ 8 hours.
	ACGIH TLV (United States, 3/2017).
	TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction
	NIOSH REL (United States, 10/2016).
	TWA: 5 mg/m³ 10 hours. Form: Mist
	STEL: 10 mg/m³ 15 minutes. Form: Mist

Appropriate engineering controls

: Use only with adequate ventilation.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

: Recommended: Splash goggles and a face shield, where splash hazard exists.

Hand protection : 4 - 8 hours (breakthrough time): Nitrile gloves.

Body protection : Recommended: Long sleeved coveralls.

Other skin protection : Recommended: Impervious boots.

Respiratory protection

: If ventilation is inadequate, use a NIOSH-certified respirator with an organic vapor cartridge and P95 particulate filter.

Section 9. Physical and chemical properties

<u>Appearance</u>		Relative density	: 0.88 to 0.89
Physical state	: Liquid.	Evaporation rate	: <1 (Butyl acetate = 1)
Color	: Amber.	Solubility	: Insoluble in the following materials: cold water and hot water.
Odor	: Mild.	Solubility in water	: Insoluble
Odor threshold	: Not available.	Partition coefficient: n-	: Not available.
pН	: Not available.	octanol/water	
		Auto-ignition temperature	: >260°C (>500°F)

Melting point : Not available.

Boiling point : Not available.

Decomposition : Not available. temperature

Flammability : Not available.

Lower and upper : Not available.

Viscosity : Not available.

Vapor pressure : <0.13 kPa (<1 mm Hg) (68°F)

explosive (flammable)

Vapor density

Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.
Incompatible materials : Not available.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

limits

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), solvent- dewaxed heavy paraffinic	LD50 Dermal	Rabbit	>5000 mg/kg	-
parameter in the second	LD50 Oral	Rat	>5000 mg/kg	-

Irritation/Corrosion

Skin: Not hazardous (per manufacturer).Eyes: Not hazardous (per manufacturer).Respiratory: Not hazardous (per manufacturer).

<u>Sensitization</u>

Skin: Not hazardous (per manufacturer).Respiratory: Not hazardous (per manufacturer).

Mutagenicity

There is no data available.

<u>Carcinogenicity</u>

There is no data available.

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely routes of : Dermal contact. Eye contact. Inhalation. Ingestion.

exposure

Section 12. Ecological information

Toxicity

There is no data available.

Persistence and degradability

There is no data available.

Bioaccumulative potential

There is no data available.

Mobility in soil

Soil/water partition coefficient (Koc) : There is no data available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Section 14. Transport information

DOT IDENTIFICATION NUMBER Not applicable. DOT proper shipping name Not applicable.

DOT Hazard Class(es) Not applicable. PG Not applicable. DOT EMER. RESPONSE GUIDE NO. Not applicable

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 4(a) final test rules: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters

TSCA 8(a) PAIR: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters TSCA 8(a) CDR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): Not determined.

Clean Water Act (CWA) 307: Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts;

Toluene; Benzene; Antimony tris[O,O-dipropyl] tris(dithiophosphate)

Clean Water Act (CWA) 311: Toluene; Benzene; Ethylenediamine; Vinyl acetate

Clean Air Act Section 602 Class I Substances : Not listed DEA List I Chemicals (Precursor Chemicals) : Not listed Clean Air Act Section 602 Class II Substances : Not listed DEA List II Chemicals (Essential Chemicals) : Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Listed

SARA 302/304

Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ethylenediamine Vinyl acetate	≤0.1 ≤0.001	Yes. Yes.	10000 1000	1337.1 129	5000 5000	668.5 644.8

SARA 304 RQ : 71335834.8 lbs / 32386469 kg [9667344.6 gal / 36594880.2 L]

SARA 311/312

Hazard classifications : SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

Composition/information on ingredients

Name	Classification
Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), hydrotreated light paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

SARA 313 : This product (does/not) contain toxic chemicals subject to the reporting requirements of SARA Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Product name	CAS number	%
Not applicable.		

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: Distillates (petroleum), hydrotreated heavy paraffinic; Distillates

(petroleum), hydrotreated light paraffinic; Distillates (petroleum), hydrotreated heavy paraffinic; Distillates

(petroleum), solvent-dewaxed heavy paraffinic

New York None of the components are listed.

: The following components are listed: Distillates (petroleum), hydrotreated heavy paraffinic; Distillates **New Jersey**

(petroleum), hydrotreated light paraffinic; Distillates (petroleum), hydrotreated heavy paraffinic; Distillates

(petroleum), solvent-dewaxed heavy paraffinic

Pennsylvania : None of the components are listed.

California Prop. 65



WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Trace Metals, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www. P65Warnings.ca.gov.

Ingredient name	, ,	Maximum acceptable dosage level
Benzene	Yes.	Yes.
Trace Metals	-	-
Toluene	-	Yes.

Section 16. Other information

: 01/15/2025 : 01/15/2025 Revision date Supersedes

: 1, 3, 15. : KMK Regulatory Services Inc. Revised Section(s) Prepared by

Notice to reader
THE INFORMATION CONTAINED IN THIS SDS RELATES ONLY TO THE SPECIFIC MATERIAL IDENTIFIED. IT DOES NOT COVER USE OF THAT MATERIAL IN COMBINATION WITH ANY OTHER
MATERIAL OR IN ANY PARTICULAR PROCESS. IN COMPLIANCE WITH 29 C.F.R. 1910.1200(g), CHS HAS PREPARED THIS SDS IN SEGMENTS, WITH THE INTENT THAT THOSE SEGMENTS BE
READ TOGETHER AS A WHOLE WITHOUT TEXTUAL OMISSIONS OR ALTERATIONS. CHS BELIEVES THE INFORMATION CONTAINED HEREIN TO BE ACCURATE, BUT MAKES NO
REPRESENTATION, GUARANTEE, OR WARRANTY, EXPRESS OR IMPLIED, ABOUT THE ACCURACY, RELIABILITY, OR COMPLETENESS OF THE INFORMATION OR ABOUT THE FITNESS OF
CONTENTS HEREIN FOR EITHER GENERAL OR PARTICULAR PURPOSES. PERSONS REVIEWING THIS SDS SHOULD MAKE THEIR OWN DETERMINATION AS TO THE MATERIAL'S
SUITABILITY AND COMPLETENESS FOR USE IN THEIR PARTICULAR APPLICATIONS.



