

DEFOAMER

Antifoam ▪ Defoaming Agent

Principal Functioning Agents:

Dimethylpolysiloxane, amorphous silica gel	10%
Constituents ineffective as a Spray Adjuvant90%
TOTAL	100%

All ingredients are exempt from tolerance requirements under 40 CFR, 180.

DO NOT FREEZE

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

PRECAUTIONARY STATEMENTS

Read label before use. Keep container tightly closed. Keep only in original container. Do not eat, drink or smoke when using this product. Avoid breathing spray. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, and eye protection.

FIRST AID

Call a poison control center or doctor immediately for treatment advice. Have the product container with you when calling a poison control center or doctor, or going for treatment.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do then continue rinsing.

IF ON SKIN OR CLOTHING: Take off contaminated clothing and wash it before reuse. Wash with plenty of soap and water.

IF SWALLOWED: Unless advised otherwise by a poison control center or doctor, have person rinse mouth with water, if able. Do not give anything by mouth to an unconscious person.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth to mouth if possible.

GENERAL INFORMATION

DEFOAMER is a water based, silicone emulsion, antifoam and defoamer.

DEFOAMER can be used to prevent foam formation or knock down existing foam.

Use rates for DEFOAMER depend directly on temperature,

WA Reg. No. 48013-20022

SN: 102620

© 2020 CHS Inc.

composition, viscosity, agitation and other various conditions; therefore rates may require adjustment for the most effective dosage. Generally, use rates are lower when used as an antifoam to prevent or reduce foam formation.

DIRECTIONS FOR USE

NET FOR AQUATIC USE

Use DEFOAMER at 1/2 - 1 ounce per 100 gallons of solution. It may be necessary to adjust the amount used according to individual conditions. In situations where foam develops after the fluid level drops, stop agitation and add the recommended dosage of DEFOAMER. When foaming develops in urea water solutions, it may be necessary to use as much as 2 ounces of DEFOAMER per 100 gallons of solution.

HANDLING AND STORAGE

DEFOAMER will become thicker in cold weather and freeze. Freeze and thaw cycles may cause the emulsion to separate. Testing has shown that freezing does not significantly affect performance. Warming and shaking the container will help restore the material to its normal consistency. Do not store near oxidizing agents.

CONTAINER DISPOSAL

Keep in original container. Do not reuse empty container. Triple rinse (or equivalent) during mixing and loading, then offer container for recycling or reconditioning, or puncture and dispose of in a sanitary landfill. Dispose of container in a safe manner in accordance with federal, state, and local regulations. Recycling decontaminated containers is the best option of container disposal.

Conditions of Sale and Warranty Limitation: The directions for use of this product reflect the opinion of experts based on field use and tests. The directions are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risks inherently associated with use of this product. Crop injury, ineffectiveness or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or use of the product in a manner inconsistent with its labeling, all of which are beyond the control of CHS or the seller. All such risks shall be assumed by the buyer. CHS warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the Directions for Use, subject to the inherent risks referred to above. CHS makes no other express or implied warranty of fitness or merchantability or any other express or implied warranty. In no case shall CHS or the seller be liable for consequential, special or indirect damages resulting from the use or handling of this product. CHS and the seller offer this product, and the Buyer and the User accept it, subject to the foregoing Conditions of Sale and Warranty, which may be varied only by agreement in writing signed by a duly authorized representative of CHS.

**NET CONTENTS:
275 Gallons (1041 L)**

